

Safer POD[®] S1 Specification Sheet

HEIGHT

- 1.2m

WEIGHT

- 68kg
- Modular construction with no section greater than 25kg

CAMERAS

- 4x HDR cameras providing a 360 degree 30m range

NIGHT VISION

- 15m infra-red night vision

AUDIO

- Local visual and audible alerts with twin high output 105dB sounders and strobes

DETECTION

- Remotely monitored at Safer Group – 24/7, 365
- 360 degree intruder detection zone
- Intelligent false alarm filtering, anti-masking and wildlife immunity

TAMPER PROTECTION/FAILURE ALERTS

- Tilt/impact sensors
- Anti-jamming & anti-masking
- 2nd battery back-up
- Tracker
- EN 50131 grade 2
- Power failure alert
- Low battery alarms

COMMUNICATION

- 2-way encrypted multi-sim cellular communication

RECORDING

- Recordings of alarm images stored in the cloud

POWER OPTIONS

- Powered by rechargeable LiFePO₄ 12v DC battery
- Solar technology - fully autonomous and providing service all year-round while saving emissions and preventing noise pollution

ADDITIONAL DEVICES

Smoke/heat/CO₂, internal confirmation cameras, scaffolding detection, water detection, water shut-off valves, cable detection, air quality, remote switches, shock/impact sensor, keypad with RFID, internal sounders, intercom, EN54 evacuation manual call points, up to 100 devices can be connected over 1700m (subject to survey).

SAFER POD[®] S1



[Make an Enquiry](#)